

Rotary Filmer 550 DII

For years, banking and financial institutions have relied on Canon Micrographics for secure and reliable methods to record bank checks. Here's another reason: the Canon Rotary Filmer 550 DII. Processing checks has never been easier. The RF550 DII automatically feeds, films and endorses (optional) up to 500 checks per minute. The simple to use control panel and film loading/removal functions are easily performed right from the front of the unit.

For ultimate productivity and convenience, the RF550 DII reduces originals at ratios up to 42:1, placing up to 14,000 checks on a single roll of 16mm film. The Duplex Mode allows you to simultaneously record both sides of a check in one easy step. Advanced indexing capabilities allow the dating and blipping of document batches for easy retrieval at a later date. And Canon's world renowned optical technology ensures the highest quality filmed images. When your needs call for high-speed, reliable check processing, you owe it to yourself to check out the new Rotary Filmer 550 DII.

Rotary Filmer 550 DII Specifications

- Type: Desktop rotary microfilmer with built-in camera unit
- Reproduction Ratio: 42X, Canon lens MC20mm 1:4
- Filming Mode: Duplex
- Film Supply: 16mm-100ft (30.5m), or thin base 125/215 ft films on standard 93mm dia.reel
- Film Takeup: Standard 93mm dia. reel
- Document Size:
 - Width: 5 1/8"- 9 1/16" (130-230mm)
 - Length: 2 3/8"- 4 11/16" (70-120mm)
 - Thickness: 0.002"- 0.01" (0.05.3mm)
- Conveyor Speed: 138ft/ min (42m/min)
- Feeder: Autofeeder with gap adjustment and side guides
- Stacker: Adjustable guide for back/forward and left /right position
- Endorser: Optional B 100 Endorser; Fixed stamping position by single impression type Die Drum 232 w/6 - digit dapter Optional Inkroller: 32 (red), 33 (black), 34 (blue), and 35 (purple)
- Exposure Control: Automatic for stabilized illumination
- Indexing:
 - 6- digit LED display Odometer counting every 5" of film run
 - 6- digit date exposure with blip on film ; 3 mode date setting is available
- Switches and Controls: On/Off switch, SPACE buttton, leader /Trailer making by SPACE button, MODE button for LED display selection, FEED ADJ button for paper count - only, DATE button for date recording
- Indications: 6- digit LED for Exposure Counter/Odometer/ Date. Film supply indicators, Film end LED, Lamp failure LED, Paper misfeed LED

- Illuminations: 2 X 60V 70W halogen lamps
- Electrical Requirements: 120 V 60Hz; 230W
- Dimensions (H x W x D): 11" x 19 3/8" x 24 9/16" (280mm x 492mm x 624mm)
- Weigth: 52lbs (24 kg)
- Operation Environment: 50°-91°F (10°-32.5°C); 80% R.H. max.