



VESICULAR DUPLICATOR MODEL 5446



16/35MM VESICULAR DUPLICATOR FEATURES PROVEN, DEPENDABLE COMPONENTS & SYSTEMS

FEATURES:

Made in the USA

- New External Temperature Controller (shown) gives exceptional control over film development parameters.
- The EXTEK 5446 utilizes the same compact design and film duplicating technology which has been proven over many years in the EXTEK family line.
- Equipped with many of the same operator convenience and safety features proven in EXTEK 5402 and 5441 duplicators.
- Duplicates 16/35mm masters at up to 180 fpm (nominal).
- Fast Warm-up time: only 5 minutes from room temperature.
- Works with all known vesicular duplicating films.
- Load your film, select your duplicating speed, and push the start button. It's that simple!
- New PreXpose option (shown) allows for exceptional gray-scale image qualities. Includes our on-line film cleaning attachment.
- Also available with optional on-line film cleaner (without preexposure) and/or power rewind.



HOUSTON FEARLESS 76, INC.[®]
203 W. Artesia Blvd., Compton CA 90220-5550 (USA)
Ph#: (310) 605-0755 * Fax#: (310) 608-1556
E-Mail: sales@houstonfearless.com * Web Site: www.houstonfearless.com





MODEL 5446 VESICULAR DUPLICATOR

SPECIFICATIONS:

FILM SIZE:	16/35mm
FILM TYPE:	All available vesicular materials
FILM ROLL DIAMETER:	9.2 inches (234mm), maximum, all spindles
DUPLICATING SPEED:	Variable, up to 180 fpm (55 m / minute)
DEVELOPER:	Heated Chamber
RESOLUTION:	180 line pairs/mm, minimum
ENVIRONMENTAL:	Operating: 60 to 80 F (16 to 26 C), 40% to 70% RH Storage: -40 to 140 F (-40 to 60 C)
VENTING:	Not required (less than 2000 watts)
ELECTRICAL:	115 VAC, 60 Hz, 20A max. 230 VAC, 50 Hz 10 A max.
DIMENSIONS:	24.8 in (630 mm) high x 35.5 in. (902 cm) wide x21.0 in (533 mm) deep
WEIGHT:	150 lbs. (68KG)

- **Foolproof self-threading system:** You can slide your film into the convenient self-threading guide slot, and the Extek 5446 does all the film threading through the exposure area for you automatically, in seconds.
- **Optional fast rewind capability:** The Extek 5446 rewinds your film master onto the original reel at speeds up to 1,000 fpm. All types of reels or cores can be accommodated by this optional system.
- **User safety features:** Light-shielded cover protects unexposed film. Lamp cover shields the operator from exposure to heat and ultraviolet light.
- **Complete family of duplicators:** A wide range of diazo and silver film duplicators for 16 thru 105mm film are available from Houston Fearless. Talk to our marketing department about a proven duplicator to meet your exact requirements.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



Houston Fearless 76, Inc.®
203 W. Artesia Blvd., Compton, CA 90220
Ph#: 310-605-0755 * 800-421-5000 * Fax#: 310-608-1556
Email: Sales@houstonfearless.com * Web Site www.houstonfearless.com/extek

