

MiniLabMaster Plus

16/35/105 mm Silver (B/W) Film Processor

Single & Dual Strand

Houston Fearless 76, Inc.

Top-Quality, Competitive Price . . .

Proven Customer Satisfaction!

- HF's new MiniLabMaster Plus provides **complete film processing control** – features micro-processor temperature controllers and digital speed readout
- **Automatic replenishment system** mixes and replenishes chemistry – eliminates guesswork – enhances film quality – improved economy
- Eliminates need for high-cost pre-mixed chemistry – uses any high-quality, off-the-shelf concentrate
- Adjustable film speed - 0 to 20 FPM (0 to 6.1 meter/m) - achieve desired film density for optimum film quality
- Durable 316L Stainless Steel Construction
- Best price/performance 16-105 mm film processors on world market today – incorporates all features expected in much larger, expensive processor – twice the processing capacity of competition at significantly lower cost per roll
- Utilizes proven technology – in use by over 500 customers worldwide



Single Strand ML-200NP

*16/35/105 mm
0 – 20 FPM
(0 – 6.1 meter/m)*



Dual Strand ML-200NDS

*16/35 mm
0 – 40 FPM
(0 – 12.2 meter/m)*

Build or Enhance Your Film Lab Today!

Houston Fearless 76, Inc.

203 W. Artesia Blvd., Compton, CA 90220 (U.S.A) • Phone (310) 605-0755 • Fax (310) 608-1556
Toll Free (800) 421-5000 • www.houstonfearless.com • sales@houstonfearless.com • An ISO 9000 Compliant Company
Europe Liaison Office: Karl G. Roome • Phone/Fax 44-181-997-3475 • kgr@hfextek.demon.uk.com

MiniLabMaster Plus

16/35/105 mm Silver (B/W) Film Processor

Single & Dual Strand

Specifications

Film Type:	Black & White
Process:	Conventional Negative
Film Sizes:	16/35/105 mm (Single Strand)
Operation:	Daylight
Output (Adjustable):	0-20 FPM (0 – 6.1 meter/m) Each Strand
Construction:	316L Stainless Steel
Power:	115V, 60 Hz, 20A
Water/Drain:	2 gpm @ 15 psi (7.6 liter/min @ 103.4 kPa)
Dryer:	Full Impingement Heating with Filtered Air
Take-Up:	1200 ft. Reel (Thin & Standard Film)
Dimensions:	Width: 41 in (1041 mm) Depth: 19.5 in (495 mm)
Recirculation/Filtration:	Developer and Fixer
Tank Sequence	Capacity in ft/gal (m/liters)
Developer	8/3 (2.44/11.4)
Rinse	4/1.5 (2.22/5.7)
Fixer 1	4/1.5 (2.22/5.7)
Fixer 2 (Counter-Current)	4/1.5 (2.22/5.7)
Wash	12/4.5 (3.66/17)
Dryer	11/- (3.35)/-



Quick-Disconnect Fittings for Easy Rack Removal, Installation



“No-Spill” Drain System



Simple Maintenance

STANDARD EQUIPMENT

Daylight Film Magazine

1200 ft. Load and Take-Up Reels

Operations & Maintenance Manual with Illustrated Parts List

Variable Speed and Microprocessor Temperature Controls

Hose Kit

Water Solenoid By-Pass

Automatic Mix and Replenishment System

OPTIONAL ACCESSORIES

Spare Parts Kit

Daylight Loader and Adapter

Silver Recovery Unit

Houston Fearless 76, Inc.

203 W. Artesia Blvd., Compton, CA 90220 (U.S.A) • Phone (310) 605-0755 • Fax (310) 608-1556

Toll Free (800) 421-5000 • www.houstonfearless.com • sales@houstonfearless.com • An ISO 9000 Compliant Company

Europe Liaison Office: Karl G. Roome • Phone/Fax 44-181-997-3475 • kgr@hfextek.demon.uk.com