



Versatile and compact, Canon's Microprinter 50 provides reliable operation and high quality plain paper output from microfiche or microfilm.

Canon's MP-50 is a powerful and versatile tool for everyday reading and printing of microfilmed images, right from your desktop. Just drop the fiche into the film carrier and you're ready to go. A series of interchangeable zoom lenses with wide magnification ranges clearly display images on the screen, perfectly positioned for optimum viewing. And with a print speed of 4 letter-size pages per minute, the MP-50 easily meets your high quality output needs. In fact, the MP-50's print engine is based on Canon's exclusive MP cartridge technology. It contains all the parts that can wear out or run out in one easy to replace unit. The MP-50 even tells you when it's time to change the cartridge. And when you do, it's like getting a whole new printer in one simple step. Built primarily for microfiche viewing and printing, an optional rollfilm carrier snaps into place for easy retrieval and output of documents stored on 16mm microfilm. So whether you store images on microfiche or microfilm, the Canon Microprinter 50 is the little printer with big capabilities for your office.

Microprinter 50 Specifications

Type: Desktop type reader-printer

Print Process: Canon MP Cartridge plain-paper process; single component dry toner projection system

Film: Negative* images of silver, vesicular or diazo film

Film Carrier: Built-in carrier for standard 4" x 6" (105mm x

148mm) fiche/jacket. Optional Roll Carrier 50 for 16mm rollfilm

Indexing: Interchangeable grid-index plates

Magnification Lenses: Slide-in type(Optional)

Zoom lens: 18-36x (CZ01), 21-42x (CZ02)

Single Magnification: 17.2x (C01), 19x (C02), 23.5x (C03), 29x (C04), 33x (C05), 35.5x (C09), 41x (C06), 47x (C07); w/Prism: 23.5x (C03P), 33x (C05P), 41x (C06P); 47x (C07P)

Image Rotation Lens: CPZ01 (for 24x document), CPZ02 (for 41x document), CPZ03 (for 47x document)

Focusing: By lens focusing fins; constant focus with floating-lens system

Image Rotation: 360 degrees by prism lenses or 90 degrees by image-rotation lenses

Print Size: 8 1/2x 11 (U.S. Letter size)

Paper Supply: Automatic stack-sheet feeding system (up to 50 sheets)

Print Speed: 4 prints per minute; warmup time 24 seconds

Multi-print: 1 - 9 with countdown indication, or "F" mode (for continuous printing of stacked paper)

Density Control: Manual Dial Adjustment

Supplies: MP Cartridge 20N

Light Source: 17V 60W halogen lamp

Warning System: Self-diagnosis with LED indication

Electrical Requirements: 120V 60Hz 1.0kW

Dimensions (H x W x D): 22 3/8" x 28 1/8" x 28 2/3" (568 x 457 x 715mm)

Weight: 62 lbs. (28 kg)

Operational Environment: 50 - 90° F, 10 - 80% RH

Accessory: Dust Cover

* For positive film only use, MP50P is available in combination use with MP Cartridge 20P