

## Microprinter 60

Canon's Microprinter 60 sets new performance standards for basic, everyday reproduction of microform images. The system offers virtually maintenance-free operation in a sleek desktop design through the use of Canon's replaceable MP20 cartridge, an all-in-one system which contains all printing consumables. Its fast print speed and increased paper supply make the MP60 the new standard for daily fiche and 16mm rollfilm applications.

### Microprinter 60 Specifications

- Type: Desktop type reader-printer
- Print Process: Canon MP Cartridge plain-paper process; single component dry toner projection system
- Film: Both negative and positive images of silver, vesicular or diazo film
- Film Carrier: Built-in carrier for standard 4" x 6" (105mm x 148mm) fiche/jacket optional Motorized Carrier 60 for 16mm rollfilm
- Indexing: Interchangeable grid-index plates for built-in fiche carrier
- Screen: 11 3/4" x 11 3/4" (300mm x 300mm) rear projection type with print frame markings and adjustable reading cursor
- Magnification Lenses (optional): Zoom Lens; 17X to 47X, Prism Lenses 23.5X, 41X, 47X
- Magnification Change: Adjustment ring for Zoom Lens: slide-in replacement of Prism Lenses
- Focusing: By Lens focusing fins: constant focus with floating-Lens system
- Image Rotation: 360 degrees by adjustment ring for prism lenses
- Print Size: 8 1/2" x 11" (Letter size)
- Paper Supply: Automatic feed by snap-in precut 250-sheet cassette
- Print Speed: 8 prints per minute: approximate warmup time 25 seconds
- Multiprint: 1-9 with LED countdown indication
- Special Print/Control Mode: Optional masking function: Reader-only mode
- Density Control: Manual slide lever adjustment: optional Automatic Exposure Control function
- Supplies: MP Cartridge 20N for negative film, 20P for positive film
- Light Source: 20V 115W halogen lamp
- Warning System: Self-diagnosis with LED indication
- Electrical Requirements: 120V 60Hz 9.2A
- Dimensions (H x W x D): 26 7/8" x 19" x 28 3/4" (682 x 485 x 729mm)
- Weight: 83lbs. (38kg)